


Uplight





Ø80mm

= = 3.45mm

SPECIFICATIONS	
Product Code	AQL-530
Family	Phoenix
Construction Material	Solid Cast Brass
Cable	1M Aqualux PLUS QuickConnect
IP Rating	IP68
Warranty	5 Year Aqualux Warranty

CONFIGURED OPTIONS

Variant CodeAQL-530-B6D00730DFQBody ColourNatural BrassControl Gear24VAC Triac DimmableRated Power7WNominal Lumens550 lmCCT / Colour3000K / 550mAOpticalDFCRI90	CONFIGURED OF HONS	
Control Gear24VAC Triac DimmableRated Power7WNominal Lumens550 lmCCT / Colour3000K / 550mAOpticalDF	Variant Code	AQL-530-B6D00730DFQ
Rated Power7WNominal Lumens550 lmCCT / Colour3000K / 550mAOpticalDF	Body Colour	Natural Brass
Nominal Lumens550 lmCCT / Colour3000K / 550mAOpticalDF	Control Gear	24VAC Triac Dimmable
CCT / Colour 3000K / 550mA Optical DF	Rated Power	7W
Optical DF	Nominal Lumens	550 lm
	CCT / Colour	3000K / 550mA
CRI 90	Optical	DF
	CRI	90
Other AqualuxPLUS QuickConnect	Other	AqualuxPLUS QuickConnect
Dimming Yes, TRIAC Primary Side	Dimming	Yes, TRIAC Primary Side

INTRODUCTION

Sharing many of the same components as the AQL-540, the AQL-530 is designed to withstand the worst conditions nature can offer. Solid cast brass with 4 finish options and epoxy encapsulated internals the AQL-530 is suitable for any application that requires the best in reliability and performance.



1300 662 644 sales@aqualux.com.au