


3000K WARM WHITE | **4000K** COOL WHITE | **5500K** NATURAL WHITE



Selector Switch



| | | | | | | | | | |
|------|-----|-------------------------|--|-------------------|---------|-------------------|-------|-------------|------|
| 240V | 30W | 3000K 4000K 5500K | | | CRI >81 | POWER FACTOR 0.99 | | | |
| | | | | 25° BEAM ANGLE | | | 175mm | INDOOR ONLY | 1.2m |

FEATURES

- Switchable between Warm White (3000K), Cool White (4000K) & Natural White (5500K), switch located on the driver.
- Dimmable.
- Rated for IC-4 Abutted and Covered usage to allow for covering with thermal insulation.
- Aluminium housing
- Adjustable snorkel design.
- External driver with flex & plug. (Total length 1.2 metre).
- Indoor use only.
- 5 Year Warranty.

APPLICATION AREAS

- Office & school lighting: office room, meeting room, class room.
- Commercial lighting: shopping mall, super market, retailer shops.
- Other situations: hospital, laboratory, dust-free workshop.



| 38W | 3000K 2800lm | 4000K 3200lm | 5500K 3000lm |
|-------|-----------------|-----------------|-----------------|
| 3.06m | 994.3lx | 1172lx | 1069lx |
| 6.13m | 248.6lx | 293.0lx | 267.1lx |
| 9.21m | 110.5lx | 130.2lx | 118.7lx |
| 12.3m | 62.14lx | 73.24lx | 66.78lx |
| 15.3m | 39.77lx | 46.88lx | 42.71lx |

| MODEL NO. | WATTAGE (W) | LUMENS @ 3000K (lm) | LUMENS @ 4000K (lm) | LUMENS @ 5500K (lm) | PRODUCT COLOUR |
|-----------|-------------|---------------------|---------------------|---------------------|----------------|
| 20458/05 | 30 | 2100 | 2400 | 2300 | WHITE |