

CANDLE LED GLOBES

- Input voltage: 240V AC 50/60Hz
- Wattage: 6W
- San'an SMD2835 LED chips
- Frosted glass globe cover
- Ambient temp: -15 to 40°C
- Not suitable for dimming

25,000
HRS

BEAM
300°

3 YEAR
WARRANTY



CODE	DESCRIPTION	TECHNICAL DATA					DIMENSIONS		
		BASE	KELVIN (K)	LUMENS (LM)	WATT (W)	CRI	LENGTH (mm)	DIAM (mm)	CARTON QTY
CAN25	6W CAN LED GLOBE ES 3000K	E27	3000	470	6=40	80	102	Ø38	1/10/100
CAN26	6W CAN LED GLOBE BC 3000K	B22	3000	470	6=40	80	101	Ø38	1/10/100
CAN27	6W CAN LED GLOBE SES 3000K	E14	3000	470	6=40	80	108	Ø38	1/10/100
CAN28	6W CAN LED GLOBE SBC 3000K	B15	3000	470	6=40	80	107	Ø38	1/10/100
CAN29	6W CAN LED GLOBE ES 5000K	E27	5000	490	6=40	80	102	Ø38	1/10/100
CAN30	6W CAN LED GLOBE BC 5000K	B22	5000	490	6=40	80	101	Ø38	1/10/100
CAN31	6W CAN LED GLOBE SES 5000K	E14	5000	490	6=40	80	108	Ø38	1/10/100
CAN32	6W CAN LED GLOBE SBC 5000K	B15	5000	490	6=40	80	107	Ø38	1/10/100



UPDATED ON 07.12.2016