

Tel: +64 9 427 6133 | Fax: +64 9 427 6134





OTTER SERIES

12V DC Waterproof Constant Voltage LED Driver IP67

• Input voltage: 170-265V 50/60Hz

• Output voltage: 12V DC


• Short Circuit, Overload and Thermal Protection

• Built in Active PFC Function


• Ambient Temperature: -30 to 50°C

• Flex & Plug Included: 1.2m









Part No.	Description	Watt	Current	Load	Min.Load per Cable	Max.Load per Cable	Product Dimensions (mm)	Box Weight (kg)	Box Dimensions (cm)	Carton QTY
OTTER1	DRIVER LED 12V DC CONSTANT VOLT	12W	0.15A	1.2-9.6W	1.2W	9.6W	65x29x20	0.26	23x7x5	1/25
OTTER5	DRIVER LED 12V DC CONSTANT VOLT	150W	12.5A	15-120W	15W	60W	210x71x46	1.1	25x11x7	1/10
OTTER7	DRIVER LED 12V DC CONSTANT VOLT	300W	25A	30-240W	30W	120W	275x95x50	2.3	30x17x8	1/5

This driver OTTER5 & OTTER7 are manufactured with a split cable format for carrying increased current for easier connection of multiple loads Each driver can be used:

- At full load capacity by connecting all cables to one terminal block
- With any combination of split cables (as long as the minimum and maximum loads below are adhered to)

FULL load capacity CANNOT be connected to one cable

^{*}Must be installed by a licenced electrician (Installation instructions sheet provided in each product box)

^{*}To avoid disappointment and warranty problems, please ensure the IP rating of the chosen product is relevant for the intended use.