

SLICK SERIES: LED Slim Downlights



**VEU
& IPART
Approved**



PRODUCT FEATURES

- Input voltage: 240V AC 50/60Hz
- LED chips: SMD2835
- Power factor: 0.9
- Material: PC
- Flex & plug: 1.2m
- Suitable for dimming
- Ambient temperature: -20 to 40°C
- 5 year domestic & 3 year commercial warranty



CODE	DESCRIPTION	KELVIN	LUMENS (LM)	WATT (W)	CRI	DIAM. (mm)	DEPTH (mm)	CUT OUT (mm)	CARTON QTY
SLICK-R3	D/L LED FIXED DIMM SLIM WH RND 3000K 12W	3000K	1000	12	82	Ø175	22	Ø155	1/20
SLICK-R5	D/L LED FIXED DIMM SLIM WH RND 3000K 18W	3000K	1500	18	82	Ø222	22	Ø205	1/20
SLICK-S1	D/L LED FIXED DIMM SLIM WH SQ 3000K 9W	3000K	700	9	82	150	22	130x130	1/20
SLICK-S2	D/L LED FIXED DIMM SLIM WH SQ 5000K 9W	5000K	800	9	82	150	22	130x130	1/20
SLICK-S5	D/L LED FIXED DIMM SLIM WH SQ 3000K 18W	3000K	1500	18	82	222	22	205x205	1/20

Tested and Recommended dimmers:

- CLIPSAL 32E450UDM • CLIPSAL 32E450TM • HPM CAT400T