



IMAGE	PART NUMBER	COLOUR TEMP	LUMENS	INPUT	INCLUDED LED
	<b>HV2960C-TTM-240V</b>	5500K	400lm	240v	Built-in 5w
	<b>HV2960W-TTM-240V</b>	3000k	360lm		
	<b>HV2960C-TTM-12V</b>	5500K	400lm	12v DC	Built-in 5w
	<b>HV2960W-TTM-12V</b>	3000k	360lm		
IMAGE	PART NUMBER	COLOUR TEMP	LUMENS	INPUT	INCLUDED LED
	<b>HV2960C-BLK-240V</b>	5500K	400lm	240v	Built-in 5w
	<b>HV2960W-BLK-240V</b>	3000k	360lm		
	<b>HV2960C-BLK-12V</b>	5500K	400lm	12v DC	Built-in 5w
	<b>HV2960W-BLK-12V</b>	3000k	360lm		
IMAGE	PART NUMBER	COLOUR TEMP	LUMENS	INPUT	INCLUDED LED
	<b>HV2961C-TTM-240V</b>	5500K	400lm	240v	Built-in 5w
	<b>HV2961W-TTM-240V</b>	3000k	360lm		
	<b>HV2961C-TTM-12V</b>	5500K	400lm	12v DC	Built-in 5w
	<b>HV2961W-TTM-12V</b>	3000k	360lm		
IMAGE	PART NUMBER	COLOUR TEMP	LUMENS	INPUT	INCLUDED LED
	<b>HV2961C-BLK-240V</b>	5500K	400lm	240v	Built-in 5w
	<b>HV2961W-BLK-240V</b>	3000k	360lm		
	<b>HV2961C-BLK-12V</b>	5500K	400lm	12v DC	Built-in 5w
	<b>HV2961W-BLK-12V</b>	3000k	360lm		

Nava Aluminium

- Surface mounted open face & eyelid step light
- Aluminium Poly Powder Coated Black And Titanium Coloured Aluminium
- Opal PC diffuser
- IP Rating: IP65



All low voltage products that specify an input of 12v or 24v DC must be used with a suitable LED driver, refer to pages 267 - 274  
Lumen output measured at source. All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to page 336

All low voltage products that specify an input of 12v or 24v DC must be used with a suitable LED driver, refer to pages 267 - 274  
Lumen output measured at source. All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to page 336