



2 light bar




4 light bar




3 light bar



3 light round plate



4 light square plate



Tivah Aluminium Black

- Adjustable spotlights
- Aluminium Poly Powder Coated Black
- 90° tilt & 270° swivel
- High output reflector to maximise light
- IP Rating: IP54

Compatible with
Tri-Colour 9in1
 HV9506 **LED Globe**
 3w, 5w, 7w




IMAGE	PART NUMBER	COLOUR TEMP	LUMENS	INPUT	INCLUDED LED
	HV4001T-2-BLK	3000K 4000K 5500K	2x 270lm 2x 285lm 2x 300lm	240v	Tri-Colour 2x 5w GU10 LED
	HV4001T-3-BLK	3000K 4000K 5500K	3x 270lm 3x 285lm 3x 300lm	240v	Tri-Colour 3x 5w GU10 LED

IMAGE	PART NUMBER	COLOUR TEMP	LUMENS	INPUT	INCLUDED LED
	HV4001T-4-BLK	3000K 4000K 5500K	4x 270lm 4x 285lm 4x 300lm	240v	Tri-Colour 4x 5w GU10 LED
	HV4001T-3-BLK-RND	3000K 4000K 5500K	3x 270lm 3x 285lm 3x 300lm	240v	Tri-Colour 3x 5w GU10 LED
	HV4001T-4-BLK-SQ	3000K 4000K 5500K	4x 270lm 4x 285lm 4x 300lm	240v	Tri-Colour 4x 5w GU10 LED

All low voltage products that specify an input of 12v or 24v DC must be used with a suitable LED driver, refer to pages 267 - 274
 Lumen output measured at source. All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to page 336

All low voltage products that specify an input of 12v or 24v DC must be used with a suitable LED driver, refer to pages 267 - 274
 Lumen output measured at source. All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to page 336