



Niche Aluminium

- Mini square LED downlight
- Aluminium Powder Coated
- Supplied with LED driver complete with flex and plug
- Cut out: 38mm
- 45° beam angle
- IP Rating: IP54



Niche Aluminium

- Mini round LED downlight
- Aluminium Powder Coated
- Supplied with LED driver complete with flex and plug
- Cut out: 38mm
- 45° beam angle
- IP Rating: IP54



IMAGE	PART NUMBER	COLOUR TEMP	LUMENS	INPUT	INCLUDED LED
	HV5701C-BLK	5500K	270lm	240v	Built-in 3w LED
	HV5701W-BLK	3000k	240lm		
IMAGE	PART NUMBER	COLOUR TEMP	LUMENS	INPUT	INCLUDED LED
	HV5701C-WHT	5500K	270lm	240v	Built-in 3w LED
	HV5701W-WHT	3000k	240lm		

IMAGE	PART NUMBER	COLOUR TEMP	LUMENS	INPUT	INCLUDED LED
	HV5702C-BLK	5500K	270lm	240v	Built-in 3w LED
	HV5702W-BLK	3000k	240lm		
IMAGE	PART NUMBER	COLOUR TEMP	LUMENS	INPUT	INCLUDED LED
	HV5702C-WHT	5500K	270lm	240v	Built-in 3w LED
	HV5702W-WHT	3000k	240lm		

All low voltage products that specify an input of 12v or 24v DC must be used with a suitable LED driver, refer to pages 267 - 274
Lumen output measured at source. All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to page 336

All low voltage products that specify an input of 12v or 24v DC must be used with a suitable LED driver, refer to pages 267 - 274
Lumen output measured at source. All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to page 336