

2in1 Dimmable Drivers

- TRIAC Dimmable LED drivers
- Triac +0-1/10V Dimming
- Constant voltage 12v or 24v DC
- Must be installed with adequate ventilation
- Suits Havit 12v or 24v DC single coloured LED strip



12V DC - IP66 WEATHERPROOF

IMAGE	PART NUMBER	INPUT POWER	OUTPUT POWER	SIZE HxWxL (mm)
	HV9661-12V30W	240v AC	12v DC 30w	(H)20x (W)32x (L)260
	HV9661-12V60W	240v AC	12v DC 60w	(H)20x (W)32x (L)300
	HV9661-12V100W	240v AC	12v DC 100w	(H)23x (W)32x (L)330

Dali Dimmable Drivers

- Dali Dimmable LED drivers
- Constant voltage 12v or 24v DC
- Must be installed with adequate ventilation
- Suits Havit 12v or 24v DC single coloured LED strip



12V DC - IP66 WEATHERPROOF

IMAGE	PART NUMBER	INPUT POWER	OUTPUT POWER	SIZE HxWxL (mm)
	HV9663-12V30W	240v AC	12v DC 30w	(H)20x (W)32x (L)260
	HV9663-12V60W	240v AC	12v DC 60w	(H)20x (W)32x (L)300
	HV9663-12V100W	240v AC	12v DC 100w	(H)23x (W)32x (L)330



24V DC - IP66 WEATHERPROOF

IMAGE	PART NUMBER	INPUT POWER	OUTPUT POWER	SIZE HxWxL (mm)
	HV9661-24V30W	240v AC	24v DC 30w	(H)20x (W)32x (L)260
	HV9661-24V60W	240v AC	24v DC 60w	(H)20x (W)32x (L)300
	HV9661-24V100W	240v AC	24v DC 100w	(H)23x (W)32x (L)330



24V DC - IP66 WEATHERPROOF

IMAGE	PART NUMBER	INPUT POWER	OUTPUT POWER	SIZE HxWxL (mm)
	HV9663-24V30W	240v AC	24v DC 30w	(H)20x (W)32x (L)260
	HV9663-24V60W	240v AC	24v DC 60w	(H)20x (W)32x (L)300
	HV9663-24V100W	240v AC	24v DC 100w	(H)23x (W)32x (L)330

All low voltage products that specify an input of 12v or 24v DC must be used with a suitable LED driver, refer to pages 267 - 274
Lumen output measured at source. All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to page 336

All low voltage products that specify an input of 12v or 24v DC must be used with a suitable LED driver, refer to pages 267 - 274
Lumen output measured at source. All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to page 336