



Long Run LED Strip Lighting

- LED flexible strip light
- Designed for long runs up to 10 metres
- Up to 130lm per watt
- CRI: ≥ 90
- Dimmable
- Peel and stick backing for initial placement
- Beam angle 120 degrees

All LED strip must be installed using anti-static measures and on an aluminium heat dissipating surface for warranty purposes (HV9705-1003, HV9705-1603 or HV9705-2003)

All IP67 LED Strip measurements do not include the end caps, please refer to Profile and LED Strip compatability chart for correct models.

When choosing LED Strip to suit profile, remember to consider the cutting increments of the strip.



Custom cut orders available.

All custom cut orders require minimum of 48hrs production time from order confirmation, plus delivery time.

See Pages 313-314
For Havit LED Profile
Compatibility Chart



All low voltage products that specify an input of 12v or 24v DC must be used with a suitable LED driver, refer to pages 267 - 274
Lumen output measured at source. All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to page 336

Long Run LED Strip Lighting



3000K - CRI: ≥ 90 - IP20 INDOOR

| IMAGE | PART NUMBER | SMD | IP RATING | LED PER METRE | LUMENS PER METRE | VOLTAGE | WATTAGE PER METRE | MAX LENGTH | CUTTING INCREMENT | SIZE WXH |
|-------|--------------------|------|-----------|---------------|------------------|---------|-------------------|------------|-------------------|----------|
| | HV9722-IP20-64-3K | 2835 | IP20 | 64 | 520lm | 24v DC | 4.8w/m | 10m | 100mm | 8x2mm |
| | HV9722-IP20-128-3K | 2835 | IP20 | 128 | 1040lm | 24v DC | 9.6w/m | 10m | 50mm | 8x2mm |
| | HV9782-IP20-64-3K | 2835 | IP20 | 64 | 1580lm | 24v DC | 14.4w/m | 10m | 100mm | 10x2mm |

4000K - CRI: ≥ 90 - IP20 INDOOR

| IMAGE | PART NUMBER | SMD | IP RATING | LED PER METRE | LUMENS PER METRE | VOLTAGE | WATTAGE PER METRE | MAX LENGTH | CUTTING INCREMENT | SIZE WXH |
|-------|--------------------|------|-----------|---------------|------------------|---------|-------------------|------------|-------------------|----------|
| | HV9722-IP20-64-4K | 2835 | IP20 | 60 | 570lm | 24v DC | 4.8w/m | 10m | 100mm | 8x2mm |
| | HV9722-IP20-128-4K | 2835 | IP20 | 120 | 1140lm | 24v DC | 9.6w/m | 10m | 50mm | 8x2mm |
| | HV9782-IP20-64-4K | 2835 | IP20 | 60 | 1720lm | 24v DC | 14.4w/m | 10m | 100mm | 10x2mm |

5500K - CRI: ≥ 90 - IP20 INDOOR

| IMAGE | PART NUMBER | SMD | IP RATING | LED PER METRE | LUMENS PER METRE | VOLTAGE | WATTAGE PER METRE | MAX LENGTH | CUTTING INCREMENT | SIZE WXH |
|-------|--------------------|------|-----------|---------------|------------------|---------|-------------------|------------|-------------------|----------|
| | HV9722-IP20-64-5K | 2835 | IP20 | 60 | 620lm | 24v DC | 4.8w/m | 10m | 100mm | 8x2mm |
| | HV9722-IP20-128-5K | 2835 | IP20 | 120 | 1240lm | 24v DC | 9.6w/m | 10m | 50mm | 8x2mm |
| | HV9782-IP20-64-5K | 2835 | IP20 | 60 | 1870lm | 24v DC | 14.4w/m | 10m | 100mm | 10x2mm |

All LED strip must be installed on an aluminium heat dissipating surface

| | | |
|-----------------|-----------------|-----------------|
| HV9705-1003 | HV9705-1603 | HV9705-2003 |
|-----------------|-----------------|-----------------|

All low voltage products that specify an input of 12v or 24v DC must be used with a suitable LED driver, refer to pages 267 - 274
Lumen output measured at source. All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to page 336