



3000K LED Strip Lighting



IP67 WEATHERPROOF

IMAGE	PART NUMBER	SMD	IP RATING	LED PER METRE	LUMENS PER METRE	VOLTAGE	WATTAGE PER METRE	MAX LENGTH	CUTTING INCREMENT	SIZE WXH
	HV9723-IP67-60-3K	3528	IP67	60	390lm	12v DC	4.8w/m	5m	50mm	14x6mm
	HV9723-IP67-120-3K	3528	IP67	120	780lm	12v DC	9.6w/m	5m	25mm	14x6mm
	HV9723-IP67-240-3K-1	3528	IP67	240	1560lm	24v DC	19.2w/m	5m	25mm	14x6mm
	HV9783-IP67-60-3K	2835	IP67	60	1200lm	12v DC	14.4w/m	5m	50mm	16x6mm



IP20 SIDE MOUNTED

IMAGE	PART NUMBER	SMD	IP RATING	LED PER METRE	LUMENS PER METRE	VOLTAGE	WATTAGE PER METRE	MAX LENGTH	CUTTING INCREMENT	SIZE WXH
	HV9723-IP20-96SM-3K	335	IP20	96	500lm	12v DC	7.7w/m	5m	33mm	6x2mm

All LED strip must be installed on an aluminium heat dissipating surface



All low voltage products that specify an input of 12v or 24v DC must be used with a suitable LED driver, refer to pages 267 - 274
Lumen output measured at source. All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to page 336

3000K LED Strip Lighting

- LED flexible strip light
- Dimmable
- Peel and stick backing for initial placement
- Beam angle 120 degrees
- All LED strip must be installed using anti-static measures and on an aluminium heat dissipating surface for warranty purposes (HV9705-1003, HV9705-1603 or HV9705-2003)

See Pages 313-314
For Havit LED Profile
Compatibility Chart



IP20 INDOOR

IMAGE	PART NUMBER	SMD	IP RATING	LED PER METRE	LUMENS PER METRE	VOLTAGE	WATTAGE PER METRE	MAX LENGTH	CUTTING INCREMENT	SIZE WXH
	HV9723-IP20-60-3K	3528	IP20	60	390lm	12v DC	4.8w/m	5m	50mm	8x2mm
	HV9723-IP20-120-3K	3528	IP20	120	780lm	12v DC	9.6w/m	5m	25mm	8x2mm
	HV9723-IP20-240-3K-1	3528	IP20	240	1560lm	24v DC	19.2w/m	5m	25mm	10x2mm
	HV9723-IP20-240-3K-2	3528	IP20	240	1560lm	24v DC	19.2w/m	5m	50mm	16x2mm
	HV9731-IP20-180-3K	2216	IP20	180	390lm	24v DC	4.8w/m	5m	33mm	4x2mm
	HV9733-IP20-180-3K	2216	IP20	180	780lm	24v DC	9.6w/m	5m	33mm	4x2mm
	HV9783-IP20-60-3K	2835	IP20	60	1200lm	12v DC	14.4w/m	5m	50mm	10x2mm
	HV9783-IP20-120-3K	2835	IP20	120	1920lm	12v DC	24w/m	5m	25mm	10x2mm
	HV9783-IP20-168-3K	2835	IP20	168	3260lm	24v DC	32.6w/m	5m	83mm	19x2mm
	HV9783-IP20-252-3K	2835	IP20	252	4140lm	24v DC	46w/m	3m	83mm	39x2mm



IP54 WATER RESISTANT

IMAGE	PART NUMBER	SMD	IP RATING	LED PER METRE	LUMENS PER METRE	VOLTAGE	WATTAGE PER METRE	MAX LENGTH	CUTTING INCREMENT	SIZE WXH
	HV9723-IP54-60-3K	3528	IP54	60	390lm	12v DC	4.8w/m	5m	50mm	8x3mm
	HV9723-IP54-120-3K	3528	IP54	120	780lm	12v DC	9.6w/m	5m	25mm	8x3mm
	HV9723-IP54-240-3K-1	3528	IP54	240	1560lm	24v DC	19.2w/m	5m	25mm	10x3mm
	HV9783-IP54-60-3K	2835	IP54	60	1200lm	12v DC	14.4w/m	5m	50mm	10x3mm

All low voltage products that specify an input of 12v or 24v DC must be used with a suitable LED driver, refer to pages 267 - 274
Lumen output measured at source. All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to page 336