



IMAGE	PART NUMBER	COLOUR TEMP	LUMENS	INPUT	INCLUDED LED
	<b>HV1429C-7W</b>	5500K	595lm	12v DC	Built-in 7w COB
	<b>HV1429W-7W</b>	3000k	560lm		
IMAGE	PART NUMBER	COLOUR TEMP	LUMENS	INPUT	INCLUDED LED
	<b>HV1429C-12W</b>	5500K	1080lm	12v DC	Built-in 12w COB
	<b>HV1429W-12W</b>	3000k	960lm		
IMAGE	PART NUMBER	COLOUR TEMP	LUMENS	INPUT	INCLUDED LED
	<b>HV1429T-24W</b>	3000K 4000K 5500K	1900lm 1970lm 2040lm	12v DC	<b>Tri-Colour</b> Built-in 24w COB

## Oasis Aluminium Black

- Single adjustable spike spotlight
- Aluminium Poly Powder Coated Black
- Spike length: 260mm
- 1m reinforced cable
- IP Rating: IP65



All low voltage products that specify an input of 12v or 24v DC must be used with a suitable LED driver, refer to pages 267 - 274  
Lumen output measured at source. All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to page 336

All low voltage products that specify an input of 12v or 24v DC must be used with a suitable LED driver, refer to pages 267 - 274  
Lumen output measured at source. All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to page 336