




Wall Down Lite


Cat. No. DL
 Cat. No. DL/R
 Cat. No. DLGU
 Cat. No. DLMH20
 Cat. No. DLMH35



Retro™



Retro™
 USA/Canada



Metal Halide



The Wall Down Lite is suitable for mounting on timber, masonry, stone, etc. non-adjustable for one way wall washing, can be mounted with the lamp directed up or down. Water resistant with a 78mm diameter mounting base, complete with stainless steel screws.

The Retro™ is a 110/240-12 ac mains option suited to an installation where mounting a transformer is a problem, e.g. a brick wall where there is only the cable protruding out of the wall and it is not an option to recess the transformer or when replacing an existing light fitting. The base size increases in size to accommodate the encapsulated IP66 dimmable transformer.

A GU10 version of this luminaire is also available for line voltage lamps. The Wall Down Lite Metal Halide is extremely energy efficient, outputting 2-3 times the light of a halogen lamp, and uses a GX10 20 or 35 watt lamp.

Ordering Information

Luminaire Type

DL - Wall Down Lite

Material/Finish

BK - Black
 BZ - Bronze
 GN - Green
 STAR - Silver Star
 WH - White
 WB - Birch
 DG - Dark Grey
 OG - Olive Green
 RG - Beige
 PR - Primrose
 COP - Copper
 SS - 316 Stainless Steel

Accessories

CJK150 - Cable Joint Kit
 LENSSTEPF - Frosted Lens
 GG - Glare Guard
 (Not for Metal Halide)
 HCL - Hex Cell Louvre Adaptor
 GU - GU10 Option
 MH - Metal Halide Option
 /R - Retro™ Transformer
 110/240-12 volt
 WBAP - Wall Box Adaptor Plate
 For LED options, refer to
 page 10.4 (dedicated LED),
 10.4.3 (6 watt), 10.4.4 (3 watt)
 or <http://hunza.co.nz/l.html>

Ordering Example:

DL BK - Wall Down Lite in Black
 DL/R SS - Wall Down Lite Retro™ in 316 Stainless Steel
 DLGU BK - Wall Down Lite GU10 in Black
 DLMH20 BK - Wall Down Lite Metal Halide 20 watt in Black
 LENSSTEPF - Frosted Lens
 (Accessories ordered separately)

HUNZA™ PURE OUTDOOR LIGHTING

HUNZA FACTORY
 130 Felton Mathew Ave
 Glen Innes
 Auckland 1072
 New Zealand

Ph: 64-9-528 9471
 Fax: 64-9-528 9361
hunza@hunza.co.nz
www.hunza.co.nz

INTERNATIONAL CONTACTS:
www.hunza.co.nz/contacts.php

Specifications may change without notice.
 Manufactured in New Zealand.
 © 2011 Hunza Holdings Ltd.

Ver 1.4

Luminaire Construction

CNC machined from the following metals:

Body: High corrosion resistant low copper 63.5mm (2½") x 10mm (25/64") aluminium. End cap - solid aluminium 63.5mm (2½") rod.

Base & Mounting Plate (Retro™): Cast from virgin high corrosion resistant CC401 low copper aluminium alloy chromate substrate and high UV resistant polyester powder coat - Black, Bronze, Green, Silver Star, White, Birch, Dark Grey, Olive Green, Beige, Primrose.

Body: Copper 63.5mm (2½") x 10mm (25/64). End cap - solid copper 63.5mm (2½") rod.

Base: Copper Hand spun 2mm (5/64")

Mounting Plate: Forged brass (Retro™)

Body: 316 Stainless Steel 63.5mm (2½") x 10mm (25/64) rod. End cap - 316 stainless steel 63.5mm (2½") rod.

Base: Investment cast and CNC machined (Retro™).

Mounting Plate: Investment cast and CNC machined.

Mounting

12 volt: The luminaire is mounted to the wall using two 316 stainless screws through a shallow base 16mm (5/8") in depth. A Wall Box Adaptor Plate is available as an accessory to fit 3.0 and 4.0 junction boxes for USA/Canada.

Retro™ 110/240-12 volt: a mounting plate is fixed to the wall using two screws, the luminaire is fitted to the mounting plate.

Features

Lens:

10mm (3/8") clear flush fit shatter resistant glass.

Lifetime Warranty.

Gasket:

Silicone, iron impregnated 220°C (428°F).

Lamp Holder:

GU5.3 & GU10 - 350°C (662°F) ceramic multi contact lamp holder with 250°C (480°F) teflon cables.

Metal Halide GX10 - 350°C (662°F) ceramic multi contact lamp holder with 250°C (480°F) teflon cables.

Accessories:

Cable Joint Kit (Cat. CJK150)

Not approved for USA/Canada.

Frosted Lens (Cat. LENSSTEPF).

Glare Guard (Cat. GG).

Hex Cell Louvre Adaptor (Cat. HCL).

GU10 Option (Cat. GU).

Metal Halide Option (Cat. MH).

Retro™ transformer 110/240-12 volt

(Cat. /R).

Wall Box Adaptor Plate (Cat. WBAP)

12 volt luminaire USA / Canada).

Standards

IP66  UL1838

Luminaire Weight

12 volt: Alum .460kg (1lb)
Cop 1.200kg (2lb 10oz)
SS 1.080kg (2lb 6oz)

Retro: Alum .780kg (1lb 11oz)
Cop 1.680kg (3lb 11oz)
SS 1.505kg (3lb 5oz)

Power Supply

HUNZA™ Inground or Wall Mount Transformer: not included.

Metal Halide - 230-240 volt ac 50Hz built in ballast

USA and Canada:

HUNZA™ Wall Mount: not included
Approved for internal use.

Metal Halide - 120 volt ac 60Hz built in ballast

RETRO™

HUNZA™ 110/240-12 volt ac potted electronic transformer built into the Retro™ base. Dimmable with a suitable dimmer.

Approved for internal use.

Luminaire: supplied with

MR16 GU5.3 20 or 35 watt lamp max.
GU10 - GU10 25 or 35 watt lamp max.

LED - Refer to previous page.










Metal Halide - GX10 20 or 35 watt lamp
USA and Canada:

MR16 GU5.3 20 or 35 watt lamp max.

GU10 Halogen - Lamp not supplied

LED - Refer to previous page.

Metal Halide - GX10 20 or 35 watt lamp



HUNZA™ PURE OUTDOOR LIGHTING

HUNZA FACTORY
130 Felton Mathew Ave
Glen Innes
Auckland 1072
New Zealand

Ph: 64-9-528 9471
Fax: 64-9-528 9361
hunza@hunza.co.nz
www.hunza.co.nz

INTERNATIONAL CONTACTS:
www.hunza.co.nz/contacts.php

Specifications may change without notice.
Manufactured in New Zealand.
© 2011 Hunza Holdings Ltd.

Ver 1.4