



The G512-LED Double Villa is a compact, adjustable, direct or indirect accent used for grazing walls or other accent illumination tasks. The luminaire is constructed from 316 marine grade stainless steel with Lumascope's proprietary ElectroPolishPlus™ surface treatment, to provide long life, even in coastal environments. This luminaire is ideal for use in modern architectural designs, and features the Lumascope d5 driver technology for advanced dimming and control options.

Performance

Static White & Colour	Lumen Output (lm)	Efficacy (lm/W)	Peak Intensity (cd)
● 3,000 K (80 CRI)	-	-	-
● 4,000 K (80 CRI)	322	92	3,695
● Blue (470nm)	-	-	-

Static white lumen output values are based on 3W luminaire with 14° lens, single head.

<b>Beam Angles</b>	14°, 25°, 30°, 40°
--------------------	--------------------

Electrical

<b>LED Power</b>	2 x 3W	
<b>Consumption</b>	2 x 3.6W	
<b>Input Voltage</b>	Low Voltage	24V DC
	Line Voltage	110-240V AC, 50/60Hz

Control

<b>Protocols</b>	PWM (0-10V to PWM, DMX to PWM and DALI to PWM converters available)
------------------	---

Physical

<b>Housing</b>	316 marine grade stainless steel
<b>Installation</b>	Wall mount
<b>Ambient Operating Temperature</b>	-10°C to +40°C (-14°F to 104°F)
<b>Surface Temperature</b>	≤65°C (≤149°F) <b>HumanTouch™</b> Compliant

Certification & Compliance


<b>IP Rating</b>	IP65
<b>Certifications</b>	CE, RCM




Luminaire Dimensions



G512-LED Double Villa  
Low Voltage



G512-LED Double Villa  
Line Voltage



G512-LED    6                SS

Power	Code
2 x 3W	6

Static White & Colour	Code
2,700 K (80 CRI)	D7
3,000 K (80 CRI)	H6
4,000 K (80 CRI)	W4
Blue (470nm typical)	B4





Beam		Code
Narrow	14°	NR
Narrow Medium	25°	NM
Medium	30°	ME
Wide	40°	WD

Finish	Code
Stainless Steel	SS


Input Voltage (International)	Code
PWM Dimmable Driver, 24V DC	D <sup>(1)</sup>
110-240V AC, 50/60Hz	M

(1) Requires appropriate power supply

Photometric data is based on test results from a NIST traceable testing lab. IES data is available at [www.lumascap.com](http://www.lumascap.com)  
 Note: No depreciation factor is applied to the data shown.



Wiring Diagram - Static Colour (DMX / DALI)



Control Protocols


- DMX**
- DALI**

For DMX control signal, use LS67100 DMX to PWM converter  
 For DALI control signal, use LSLED-RGBDIM-DALI converter

Up to 20 luminaires per run under the following conditions:

- Up to three (3) individually addressed dimmable channels
- Up to 20 luminaires per dimmable channel
- Luminaires driven by integral LED drivers
- Luminaires powered through individual power supplies or
- Luminaires powered through LS67100 PWM controller only (up to 100W total)
- Refer to 'Maximum Circuit Load' table for circuit limitations
- Always observe local electrical codes for branch circuit current limitations

Wiring Diagram - Static Colour (0-10V)



Control Protocols

- 0-10V**

For 0-10V control signal, use LS6125-2 0-10V to PWM converter

Up to 50 luminaires per run under the following conditions:

- Stand alone static colour dimming solution
- Up to 50 luminaires dimmed together
- Luminaires driven by integral LED drivers using LS6122 wall plate dimmer
- Luminaires powered through individual or shared power supplies
- Refer to 'Maximum Circuit Load' table for circuit limitations
- Always observe local electrical codes for branch circuit current limitations

Maximum Circuit Load

Compatibility with each driver is indicated by the value shown in the table, representing the maximum number of luminaires that may be powered from each driver based on a maximum cable run of 100m (328ft) and a trunk cable size of 3.3mm<sup>2</sup>. Please note, this does not take into consideration voltage drop beyond a distance of 100m or ampacity limits of the branch circuit. For assistance, please consult factory.

LSLED-24V Power Supplies	
Input Voltage	100-240V, 50/60Hz
Output Voltage	24V DC
Wattage	100W
G512-LED, 2 x 3W	10

NOTE: The above diagrams are intended to show electrical pathways between luminaires and ancillary device. These diagrams are not intended to show type or colour of cord / wire, luminaire input voltage rating, wire gauge or approved use of the cord / wire supplied with luminaires.

## Power Supply Specifications

### DC Power Supplies

#### LSLED-24V100W240

##### 24V DC Ripple Free Power Supply

Input	170-250V AC, 50/60Hz
Output	100W, 24V DC, 4.2A
Ambient Temperature Rating	-10°C to 50°C
Compliance	IEC61347-2-13, CE
IP Rating	IP66
Short Circuit Protection	Yes
Open Circuit Protection	Yes
Protection Class	Class II CE

#### LSLED-24V150W240

##### 24V DC Ripple Free Power Supply

Input	90-305V AC, 50/60Hz
Output	150W, 24V DC, 6.3A
Ambient Temperature Rating	-10°C to 50°C
Compliance	IEC61347-2-13, CE
IP Rating	IP66
Short Circuit Protection	Yes
Open Circuit Protection	Yes
Protection Class	Class II CE

#### LSLED-24V40W240

##### Electronic DC Power Supply - wall mounted

Input	100-240V AC, 50/60Hz
Rating	40W / 1.67A
Output	24V
Ambient Temperature Rating	-25°C to 60°C (-13°F to 140°F)
Output Circuits	1
Approvals	CE, EN60950-1, EN61347-2-13
IP Rating	IP65/67
Dimensions	H 171mm W 62mm L 37mm (H 6.7" / W 2.4" / L 1.5")
Weight	0.7kg (1.6lb)

## Control Related Equipment

#### LS6125-2

##### 0-10V to PWM translator - wall mounted

Input	100-240V AC, 50/60Hz
Rating	20W / 0.83A
Output	24V
Ambient Temperature Rating	-10°C to 50°C
Open Circuits	1
Control Protocol	0-10V
Approvals	CE
IP Rating	IP65/67
Dimensions	H 204mm W 166mm L 91mm (H 8.0" / W 6.5" / L 3.6")
Weight	0.5kg (1.1lb)

#### LS67100

##### DMX to PWM translator

Input	24V DC
Rating	4 x 60W max
Output	4 x 2.5A max
Open Circuits	4
Approvals	CE, UL
IP Rating	IP65
Dimensions	H 286mm W 117mm L 82mm (H 11.25" / W 4.6" / L 3.2")
Weight	0.2kg (0.5lb)

**Control Related Equipment cont...**

LSLED-RGBDIMDALI

DALI converter

<b>Input</b>	24V DC
<b>Rating</b>	30W max
<b>Output</b>	24V DC PWM (Inverted)
<b>Ambient Temperature Rating</b>	50°C
<b>Output Channels</b>	3
<b>Control Protocol</b>	DMX512A, DALI, DSI, RDM
<b>Approvals</b>	CE Ctick EN6137-1 , EN61347-2-13, IEC 62384
<b>IP Rating</b>	IP67
<b>Weight</b>	0.75kg