



# BARLOW

## 6 PENDANT



<b>Voltage</b>	240v	<b>Color</b>	NICKEL MATTE / OPAL GLASS											
<b>Wattage</b>	25w max		BLACK MATTE / OPAL GLASS											
<b>Light source</b>	6 x E14													
<b>Light source Lumen</b>														
<b>Type</b>		<b>Material</b>	Aluminium / Glass	<table border="1"> <tr> <td><b>Barcodes</b></td> <td></td> </tr> <tr> <td><b>BARLOW PE6-BK</b></td> <td>9329501048108</td> </tr> <tr> <td><b>BARLOW PE6-NK</b></td> <td>9329501048115</td> </tr> <tr> <td><b>Parts</b></td> <td></td> </tr> <tr> <td><b>RG CUTLER - OP</b></td> <td>9329501048481</td> </tr> </table>	<b>Barcodes</b>		<b>BARLOW PE6-BK</b>	9329501048108	<b>BARLOW PE6-NK</b>	9329501048115	<b>Parts</b>		<b>RG CUTLER - OP</b>	9329501048481
<b>Barcodes</b>														
<b>BARLOW PE6-BK</b>	9329501048108													
<b>BARLOW PE6-NK</b>	9329501048115													
<b>Parts</b>														
<b>RG CUTLER - OP</b>	9329501048481													
<b>Control gear</b>														
<b>Dimmable</b>	No	<b>On/offswitch</b>	No											
<b>PF</b>		<b>Connection</b>	HARDWIRE											
<b>FIXTURE Lumen</b>		<b>Mounting</b>	SURFACE MOUNTED											
<b>LOR</b>		<b>Protection</b>	IP20											
<b>Cd</b>		<b>Class</b>	1											
<b>Beam angle</b>	360	<b>Lifetime</b>												
<b>Ra</b>		<b>Warranty</b>	1 years limited											
<b>PE Width</b>	xxx	<b>Standards</b>	Non prescribed article											
<b>PE Length</b>	1100		assembled to											
<b>Glass Dimension</b>	D:80 x H:180		AS/NZS 61347.2.3-2004-29.4.2008											
<b>Base dimension</b>	xxx		There are no interference											
<b>Base height</b>	xxx		devices and are deemed											
<b>Cable</b>			to comply with											
<b>Rod</b>	2 x 600mm, 1 x 900mm		AS/NZS CISPR 15:2002											