

LED emergency batten, IP65



°C

Item Code	SP210WPTC-EMG/SEN
Sensor	Starlux sensor
Input Voltage	220-240AC
Frequency	50/60Hz
Size of the Lamp	655*130*88mm
Material	Metal + PS
Operating Temp	0~40°C
AC Stage LED Power	2*10W LED Strip
DC Stage Light Source	DC wattage:2.5W
Battery	6.4V 1500mAh LiFePO4
Charge Time	16 hours
Discharge Time	2 hours
Emergency Lumen	1800lm
LED Lifespan	40,000 hours
Work Mode	Maintain
Installation	Surface Mounting
Indicator	Red-Charging
Test	Manual Test Switch
Connection	Terminal Block
Protection	Over-Charge /Over-Discharge
Classification	C0:D40,C90:D25
Standard	AS2293.3 IEC60598-2-22
IK	IK08
Ingress Protection(IP):	IP65

LED emergency batten, IP65



Item Code	SP220WPTC-EMG/SEN
Sensor	Starlux sensor
Input Voltage	220-240AC
Frequency	50/60Hz
Size of the Lamp	1265*130*88mm
Material	Metal + PS
Operating Temp	0~40°C
AC Stage LED Power	2*20W LED Strip
DC Stage Light Source	DC wattage:5W
Battery	6.4V 3000mAh LiFePO4
Charge Time	16 hours
Discharge Time	2 hours
Emergency Lumen	3600lm
LED Lifespan	40,000 hours
Work Mode	Maintain
Installation	Surface Mounting
Indicator	Red-Charging
Test	Manual Test Switch
Connection	Terminal Block
Protection	Over-Charge /Over-Discharge
Classification	C0:D80,C90:D63
Standard	AS2293.3 IEC60598-2-22
IK	IK08
Ingress Protection(IP):	IP65



Ta 0°C-40°C



Tested By



Certified By



APPROVALS
AS/NZS 2293 CERTIFIED