



500 Series

VBLFL-70W-4-40



Vibe 70W LED Flood 4K IP65 with 2M Flex & Plug

Features & Benefits


- Advanced input under/over voltage protection for improved reliability
- Equipped with SMALITE high voltage LED chips
- Available in Black trim only
- Breather valve allows to adjust the floodlights capacity pressure to avoid the formation of water vapour inside the fitting
- Comes complete with 2M flex & plug
- IP66 rated
- 50,000 hour lifespan
- 3 year warranty

Specifications

Luminaire efficacy EAN 9340994016993 Light Colour Cool White Wattage 70 W Lumen output IP rating 66 CRI Beam Angle 70 Degrees Trim colour Black Length 254 mm Width 42 mm Height 232 mm Lifespan 50000 Hours Warranty 3 Years LED source Material Powder coated die-cast aluminium Lamp Type Input voltage Veatherproof Veatherproof Veatherproof		
Light Colour Cool White Wattage 70 W Lumen output 6650 lm IP rating 66 CRI 80 Beam Angle Trim colour Black Length 254 mm Width 42 mm Height 232 mm Lifespan 50000 Hours Warranty 3 Years LED source Material Powder coated die-cast aluminium Lamp Type Input voltage Wiring method Powder Cobe Flex & Plug	SKU	VBLFL-70W-4-40
Light Colour Wattage To W Lumen output 6650 lm IP rating 66 CRI Beam Angle Trim colour Length Width 42 mm Height Lifespan Source Material Lamp Type Input voltage To W Moder coaled die-cast aluminium Lifex & Plug Flex & Plug	Luminaire efficacy	95 lm/W
Wattage 70 W Lumen output 6650 lm IP rating 66 CRI 80 Beam Angle 70 Degrees Trim colour Black Length 254 mm Width 42 mm Height 232 mm Lifespan 50000 Hours Warranty 3 Years LED source Smalite Material Powder coated die-cast aluminium Lamp Type LED Input voltage 220V-265V AC 50hz Wiring method Flex & Plug	EAN	9340994016993
Lumen output IP rating 66 CRI Beam Angle 70 Degrees Trim colour Black Length 254 mm Width 42 mm Height 232 mm Lifespan 50000 Hours Warranty 3 Years LED source Material Lamp Type Input voltage Wiring method 6650 lm 6650 lm 6650 lm 80 80 80 80 80 80 81 80 81 80 81 81	Light Colour	Cool White
IP rating 66 CRI 80 Beam Angle 70 Degrees Trim colour Black Length 254 mm Width 42 mm Height 232 mm Lifespan 50000 Hours Warranty 3 Years LED source Smalite Material Powder coated die-cast aluminium Lamp Type LED Input voltage 220V-265V AC 50hz Wiring method Flex & Plug	Wattage	70 W
CRI 80 Beam Angle 70 Degrees Trim colour Black Length 254 mm Width 42 mm Height 232 mm Lifespan 50000 Hours Warranty 3 Years LED source Smalite Material Powder coated die-cast aluminium Lamp Type LED Input voltage 220V-265V AC 50hz Wiring method Flex & Plug	Lumen output	6650 lm
Beam Angle Trim colour Black Length 254 mm Width 42 mm Height 232 mm Lifespan 50000 Hours Warranty 3 Years LED source Smalite Material Powder coated die-cast aluminium Lamp Type Input voltage Wiring method Place Flex & Plug	IP rating	66
Trim colour Length 254 mm Width 42 mm Height 232 mm Lifespan 50000 Hours Warranty 3 Years LED source Smalite Material Powder coated die-cast aluminium Lamp Type Input voltage Viring method Black Black Black Black Black Black Black Black Black Black B	CRI	80
Length 254 mm Width 42 mm Height 232 mm Lifespan 50000 Hours Warranty 3 Years LED source Smalite Material Powder coated die-cast aluminium Lamp Type LED Input voltage 220V-265V AC 50hz Wiring method Flex & Plug	Beam Angle	70 Degrees
Width 42 mm Height 232 mm Lifespan 50000 Hours Warranty 3 Years LED source Smalite Material Powder coated die-cast aluminium Lamp Type LED Input voltage 220V-265V AC 50hz Wiring method Flex & Plug	Trim colour	Black
Height 232 mm Lifespan 50000 Hours Warranty 3 Years LED source Smalite Material Powder coated die-cast aluminium Lamp Type LED Input voltage 220V-265V AC 50hz Wiring method Flex & Plug	Length	254 mm
Lifespan 50000 Hours Warranty 3 Years LED source Smalite Material Powder coated die-cast aluminium Lamp Type LED Input voltage 220V-265V AC 50hz Wiring method Flex & Plug	Width	42 mm
Warranty Begin Surce Smalite Material Powder coated die-cast aluminium Lamp Type LED Input voltage 220V-265V AC 50hz Wiring method Flex & Plug	Height	232 mm
LED source Material Lamp Type Input voltage Wiring method Smalite Powder coated die-cast aluminium LED 220V-265V AC 50hz Flex & Plug	Lifespan	50000 Hours
Material Powder coated die-cast aluminium Lamp Type LED Input voltage 220V-265V AC 50hz Wiring method Flex & Plug	Warranty	3 Years
lamp Type LED Input voltage 220V-265V AC 50hz Wiring method Flex & Plug	LED source	Smalite
Input voltage 220V-265V AC 50hz Wiring method Flex & Plug	Material	
Wiring method Flex & Plug	Lamp Type	LED
	Input voltage	220V-265V AC 50hz
Weatherproof Weatherproof	Wiring method	Flex & Plug
	Weatherproof	Weatherproof
Working temperature -30°C ~ 45°C	Working temperature	-30°C ~ 45°C
Box Qty 12	Box Qty	12
Kelvin 4000K	Kelvin	4000K



Dimensional Drawings



Photometric information available upon request.

