



VIBE 14W LED GOLBE 5000K B22 TRIAC DIMMABLE

VBLG-BC-14W-3KD



Vibe 14W LED, Warm White Globes are available in both an ES or BC base and with a lumen output of 108 lumens per watt, they offer a supreme light output that is ideal for many applications that require a bright lighting solution. Great for storage areas, bollards, wall fittings in a variety of industries including Farming, Aged Care and more.

Features & Benefits


- 14W
- 3K | 5K
- ES | BC
- Dimmable
- 25,000 hour lifespan
- 2 year warranty

Specifications

Luminaire efficacy EAN 9359682000107 Light Colour Warm White Wattage 14 W Lumen output 1520 Im IP rating 20 CRI 80 Beam Angle Base Type B22 Diameter 60 mm Height 119 mm Lifespan 25000 Hours Warranty 2 Years Dimmable Shatterproof LED source Material Lamp Type LED Dimming Input voltage Box Qty 100 Kelvin Varnaty PSE Im/W Warm White Warm White 14 W Lifes Dim 1520 Im 1520 Im 20 CRI 80 Box Qty 1520 Im 20 LeD LeD Dimming Triac Dimming Indoor Use Only Kelvin 3000K		
Light Colour Warm White Wattage 14 W Lumen output 1520 Im IP rating 20 CRI 80 Beam Angle Base Type B22 Diameter 60 mm Height 119 mm Lifespan 25000 Hours Warranty 2 Years Dimmable Shatterproof LED source Material Lamp Type LED Dimming Input voltage Working temperature Box Qty 14 W Warm White Warm White H4 W Warm White 1520 Im War B0 80 B0 80 B0 80 B0 80 B0 80 B0	SKU	VBLG-BC-14W-3KD
Light Colour Wattage 14 W Lumen output 1520 lm IP rating 20 CRI 80 Beam Angle 180 Degrees Base Type B22 Diameter 60 mm Height 119 mm Lifespan 25000 Hours Warranty 2 Years Dimmable Shatterproof Non-shatterproof LED source SMD Material ALUMINIUM+PC Lamp Type LED Dimming Input voltage Working temperature Box Qty 100	Luminaire efficacy	95 lm/W
Wattage 14 W Lumen output 1520 lm IP rating 20 CRI 80 Beam Angle 180 Degrees Base Type B22 Diameter 60 mm Height 119 mm Lifespan 25000 Hours Warranty 2 Years Dimmable Dimmable Shatterproof Non-shatterproof LED source SMD Material ALUMINIUM+PC Lamp Type LED Dimming Triac Dimming Input voltage 220V-240V AC 50HZ Weatherproof Indoor Use Only Working temperature -20-50 Box Qty 100	EAN	9359682000107
Lumen output IP rating CRI Beam Angle Base Type B22 Diameter 60 mm Height 119 mm Lifespan 25000 Hours Warranty Dimmable Shatterproof LED source Material Lamp Type Lied Dimming Input voltage Working temperature Jenus 20 AUMINIUM + PC Lamp Type Lied Li	Light Colour	Warm White
IP rating 20 CRI 80 Beam Angle 180 Degrees Base Type B22 Diameter 60 mm Height 119 mm Lifespan 25000 Hours Warranty 2 Years Dimmable Dimmable Shatterproof Non-shatterproof LED source SMD Material ALUMINIUM+PC Lamp Type LED Dimming Triac Dimming Input voltage 220V-240V AC 50HZ Weatherproof Indoor Use Only Working temperature -20-50 Box Qty 100	Wattage	14 W
Beam Angle Base Type B22 Diameter 60 mm Height 119 mm Lifespan 25000 Hours Warranty 2 Years Dimmable Shatterproof LED source Material Lamp Type Dimming Input voltage Working temperature Box Qty B22 B22 B22 B22 B22 B22 B22 B2	Lumen output	1520 lm
Beam Angle Base Type B22 Diameter 60 mm Height 119 mm Lifespan 25000 Hours Warranty 2 Years Dimmable Dimmable Shatterproof LED source Material Lamp Type LED Dimming Input voltage Working temperature Box Qty B22 B22 B22 B22 B22 B22 B22 B	IP rating	20
Base Type B22 Diameter 60 mm Height 119 mm Lifespan 25000 Hours Warranty 2 Years Dimmable Dimmable Shatterproof Non-shatterproof LED source SMD Material ALUMINIUM+PC Lamp Type LED Dimming Triac Dimming Input voltage 220V-240V AC 50HZ Weatherproof Indoor Use Only Working temperature -20-50 Box Qty 100	CRI	80
Diameter 60 mm Height 119 mm Lifespan 25000 Hours Warranty 2 Years Dimmable Dimmable Shatterproof Non-shatterproof LED source SMD Material ALUMINIUM+PC Lamp Type LED Dimming Triac Dimming Input voltage 220V-240V AC 50HZ Weatherproof Indoor Use Only Working temperature -20-50 Box Qty 100	Beam Angle	180 Degrees
Height 119 mm Lifespan 25000 Hours Warranty 2 Years Dimmable Dimmable Shatterproof Non-shatterproof LED source SMD Material ALUMINIUM+PC Lamp Type LED Dimming Triac Dimming Input voltage 220V-240V AC 50HZ Weatherproof Indoor Use Only Working temperature -20-50 Box Qty 100	Base Type	B22
Lifespan 25000 Hours Warranty 2 Years Dimmable Dimmable Shatterproof Non-shatterproof LED source SMD Material ALUMINIUM+PC Lamp Type LED Dimming Triac Dimming Input voltage 220V-240V AC 50HZ Weatherproof Indoor Use Only Working temperature -20-50 Box Qty 100	Diameter	60 mm
Warranty Dimmable Dimmable Shatterproof Non-shatterproof LED source SMD Material ALUMINIUM+PC Lamp Type LED Dimming Input voltage Veatherproof Undoor Use Only Working temperature Box Qty Dimmable Shatterproof Non-shatterproof SMD ALUMINIUM+PC LED Dimming Triac Dimming Input voltage 220V-240V AC 50HZ Weatherproof Indoor Use Only	Height	119 mm
Dimmable Shatterproof Non-shatterproof LED source SMD Material ALUMINIUM+PC Lamp Type LED Dimming Input voltage Veatherproof Working temperature Box Qty Dimmable Dimmable ALUMINIUM+PC LED LED Dimming Triac Dimming Indoor Use Only Vorking temperature -20-50 100	Lifespan	25000 Hours
Shatterproof LED source SMD Material ALUMINIUM+PC Lamp Type LED Dimming Input voltage 220V-240V AC 50HZ Weatherproof Indoor Use Only Working temperature -20-50 Box Qty Non-shatterproof SMD ALUMINIUM+PC LED Dimming Triac Dimming Input voltage -20-50 Box Qty 100	Warranty	2 Years
LED source Material ALUMINIUM+PC Lamp Type LED Dimming Input voltage 220V-240V AC 50HZ Weatherproof Indoor Use Only Working temperature -20-50 Box Qty SMD ALUMINIUM+PC LED Triac Dimming Input voltage 220V-240V AC 50HZ Indoor Use Only 100	Dimmable	Dimmable
Material ALUMINIUM+PC Lamp Type LED Dimming Triac Dimming Input voltage 220V-240V AC 50HZ Weatherproof Indoor Use Only Working temperature -20-50 Box Qty 100	Shatterproof	Non-shatterproof
Lamp Type Dimming Input voltage Veatherproof Working temperature Box Qty LED Triac Dimming 220V-240V AC 50HZ Indoor Use Only -20-50	LED source	SMD
Dimming Triac Dimming Input voltage 220V-240V AC 50HZ Weatherproof Indoor Use Only Working temperature -20-50 Box Qty 100	Material	ALUMINIUM+PC
Input voltage 220V-240V AC 50HZ Weatherproof Indoor Use Only Working temperature -20-50 Box Qty 100	Lamp Type	LED
Weatherproof Indoor Use Only Working temperature -20-50 Box Qty 100	Dimming	Triac Dimming
Working temperature -20-50 Box Qty 100	Input voltage	220V-240V AC 50HZ
Box Qty 100	Weatherproof	Indoor Use Only
	Working temperature	-20-50
Kelvin 3000K	Box Qty	100
	Kelvin	3000K



Dimensional Drawings



Photometric information available upon request.

