



## Oyster-LED Lights-Switchable

### VBLOY-290-16W-CCT



Our 290mm, 16W LED Oyster Lights provide a circular flush ceiling mount. Common as a replacement for Fluorescent light fittings, these lights are seen often in hotels, motels and aged care facilities. Equipped with genuine EPISTAR LED Chips, this light is 3CCT offering you the opportunity to switch between a Warm White, Cool White or Natural Light. Includes a 50,000 hour lifespan and a 3 year warranty.

#### **Features & Benefits**

- Circular flush mount ceiling LED Oyster Light
- Equipped with genuine EPISTAR LED chips
- Opal PMMA diffuser, powder coated steel base
- IP20 rated
- 50,000 hours lifespan
- 3 years warranty



# Oyster-LED Lights-Switchable

#### VBLOY-290-16W-CCT

### **Specifications**

SKUVBLOY-290-16W-CCTLuminaire efficacy95 lm/WEAN9340994020150Light Colour3CCTWattage16 WLumen output1520 lmIP rating20CRI80Beam Angle120 DegreesTrim colourWhiteDiameter290 mmWidth85 mmKifespan50000 HoursWarranty3 YearsDinmableNon-DimmableMounting typeSuffaceLED sourceEpistarLamp TypeLEDInput voltage0palWiring methodHardwireWartantpoofAngleMaterial0palMourting typeSuffaceString method0palMaterpoofNon-UnwareMaterpoofSourceMaterpoofCoyeC~40°C		
EAN9340994020150Light Colour3CCTWattage16 WLumen output1520 lmIP rating20CRI80Beam Angle120 DegreesTrim colourWhiteDiameter290 mmWidth85 mmLifespan50000 HoursWarranty3 YearsDimmableNon-DimmableMounting typeEpistarLED sourceEpistarLamp TypeLEDInput voltage0oyl - 240V ACWiring methodHardwireWeatherproofIndoor Use Only	SKU	VBLOY-290-16W-CCT
Light Colour3CCTWattage16 WLumen output1520 lmIP rating20CRI80Beam Angle120 DegreesTrim colourWhiteDiameter290 mmWidth85 mmLifespan50000 HoursWarranty3 YearsDimmableNon-DimmableMounting typeSurfaceLED sourceEpistarMaterial100V - 240V ACDiffuserOpalWiring methodHardwireWeatherproofIndoor Use Only	Luminaire efficacy	95 lm/W
Wattage16 WLumen output1520 lmIP rating20CRI80Beam Angle120 DegreesTrim colourWhiteDiameter290 mmWidth85 mmLifespan50000 HoursWarranty3 YearsDimmableNon-DimmableMounting typeSurfaceLED sourceEpistarMaterial100V - 240V ACDiffuserOpalWiring methodHardwireWeatherproofIndoor Use Only	EAN	9340994020150
Lumen output1520 lmIP rating20CRI80Beam Angle120 DegreesTrim colourWhiteDiameter290 mmWidth85 mmLifespan50000 HoursWarranty3 YearsDimmableNon-DimmableMounting typeEpistarLED sourceEpistarMaterial100V - 240V ACDiffuserOpalWiring methodHardwireWeatherproofIndoor Use Only	Light Colour	3CCT
IP rating20IP rating20CRI80Beam Angle120 DegreesTrim colourWhiteDiameter290 mmWidth85 mmLifespan50000 HoursWarranty3 YearsDimmableNon-DimmableMounting typeSurfaceLED sourceEpistarMaterial100V - 240V ACInput voltage100V - 240V ACWiring methodHardwireWeatherproofIndoor Use Only	Wattage	16 W
IteIteCRI80Beam Angle120 DegreesTrim colourWhiteDiameter290 mmWidth85 mmLifespan50000 HoursWarranty3 YearsDimmableNon-DimmableMounting typeSurfaceLED sourceEpistarMaterial100V - 240V ACInput voltage100V - 240V ACDiffuserOpalWiring methodHardwireWeatherproofIndoor Use Only	Lumen output	1520 lm
Beam Angle120 DegreesTrim colourWhiteDiameter290 mmWidth85 mmLifespan50000 HoursWarranty3 YearsDimmableNon-DimmableMounting typeSurfaceLED sourceEpistarMaterial100V - 240V ACInput voltageOpalWiring methodHardwireWeatherproofIndoor Use Only	IP rating	20
Trim colourWhiteDiameter290 mmWidth85 mmLifespan50000 HoursWarranty3 YearsDimmableNon-DimmableMounting typeSurfaceLED sourceEpistarMaterial100V - 240V ACInput voltageOpalWiring methodHardwireWeatherproofIndoor Use Only	CRI	80
Diameter290 mmWidth85 mmLifespan50000 HoursWarranty3 YearsDimmableNon-DimmableMounting typeSurfaceLED sourceEpistarMaterialPMMA Diffuser, Powder Coated Steel BaseLamp TypeLEDInput voltage00V - 240V ACDiffuserOpalWiring methodHardwireWeatherproofIndoor Use Only	Beam Angle	120 Degrees
Width85 mmLifespan50000 HoursWarranty3 YearsDimmableNon-DimmableMounting typeSurfaceLED sourceEpistarMaterialIEDInput voltage100V - 240V ACDiffuserOpalWiring methodHardwireWeatherproofIndoor Use Only	Trim colour	White
Lifespan500 MoursLifespan50000 HoursWarranty3 YearsDimmableNon-DimmableMounting typeSurfaceLED sourceEpistarMaterialPMMA Diffuser, Powder Coated Steel BaseLamp TypeLEDInput voltage100V - 240V ACDiffuserOpalWiring methodHardwireWeatherproofIndoor Use Only	Diameter	290 mm
Warranty3 YearsDimmableNon-DimmableMounting typeSurfaceLED sourceEpistarMaterialPMMA Diffuser, Powder Coated Steel BaseLamp TypeLEDInput voltage100V - 240V ACDiffuserOpalWiring methodHardwireWeatherproofIndoor Use Only	Width	85 mm
DimmableNon-DimmableMounting typeSurfaceLED sourceEpistarMaterialPMMA Diffuser, Powder Coated Steel BaseLamp TypeLEDInput voltage100V - 240V ACDiffuserOpalWiring methodHardwireWeatherproofIndoor Use Only	Lifespan	50000 Hours
Mounting typeSurfaceLED sourceEpistarMaterialPMMA Diffuser, Powder Coated Steel BaseLamp TypeLEDInput voltage100V - 240V ACDiffuserOpalWiring methodHardwireWeatherproofIndoor Use Only	Warranty	3 Years
LED sourceEpistarMaterialPMMA Diffuser, Powder Coated Steel BaseLamp TypeLEDInput voltage100V - 240V ACDiffuserOpalWiring methodHardwireWeatherproofIndoor Use Only	Dimmable	Non-Dimmable
MaterialPMMA Diffuser, Powder Coated Steel BaseLamp TypeLEDInput voltage100V - 240V ACDiffuserOpalWiring methodHardwireWeatherproofIndoor Use Only	Mounting type	Surface
MaterialSteel BaseLamp TypeLEDInput voltage100V - 240V ACDiffuserOpalWiring methodHardwireWeatherproofIndoor Use Only	LED source	Epistar
Input voltage100V - 240V ACDiffuserOpalWiring methodHardwireWeatherproofIndoor Use Only	Material	
Diffuser Opal   Wiring method Hardwire   Weatherproof Indoor Use Only	Lamp Type	LED
Wiring method Hardwire   Weatherproof Indoor Use Only	Input voltage	100V - 240V AC
Weatherproof Indoor Use Only	Diffuser	Opal
	Wiring method	Hardwire
Working temperature -20°C~40°C	Weatherproof	Indoor Use Only
	Working temperature	-20°C~40°C

0

Photometric information available upon request.

